



# PRODUCT CATALOGUE

## **NUCO Inc.**

Incorporated in 1988, NUCO Inc. has grown to be a leader in the manufacturing of silicone technology and other quality products. Located in Guelph, Ontario just west of Toronto; NUCO supplies product through distribution to various markets world wide. Some markets include: residential, HVAC, OEM, industrial and construction supply.

Our complete line of products includes:

- Acetoxy silicone sealants
- Neutral cure silicone sealants
- Paintable sealants
- Polyurethane foams
- Silicone firestops
- Epoxy sticks

## **Need More Information?**

*NUCO Inc Website*

Visit us at [www.NUCOinc.com](http://www.NUCOinc.com) for more information about the products seen in this guide, as well as new products being created throughout the year. Safety Data Sheets (SDS), as well as Technical Data Sheets (TDS) are available at the click of a button. You may also find exciting promotions, and other important news updates in our newsletter.

Visit us today at [www.NUCOinc.com](http://www.NUCOinc.com), like us on Facebook and follow us on Twitter.

**NuFlex**<sup>®</sup>  
SEALANTS

**ULTRASEAL**<sup>®</sup>  
PU FOAMS

**SELF-SEAL**<sup>®</sup>  
FIRESTOPPING PRODUCTS



## **Sales & Orders**

[Sales@nucoinc.com](mailto:Sales@nucoinc.com)

## **General Inquiries**

[Info@nucoinc.com](mailto:Info@nucoinc.com)

## **Marketing**

[Marketing@nucoinc.com](mailto:Marketing@nucoinc.com)

## **NUCO Brand**

NuFlex™ offers QUALITY sealants and STRONG construction adhesives. UltraSeal™ offers PERFORMANCE polyurethane foams and Self-Seal™ offers DEPENDABLE silicone firestops. Each brand is supported by NUCO's outstanding service and support.

## **NUCO Support**

Service, support and quality are the foundations of our company. Our customer service team is diligent, efficient and ready to help you do business with us. Our support team includes strategically placed sales representatives, technical gurus, and marketing experts. We strive to exceed our customer's expectations and have the best customer service, sales, marketing, and manufacturing teams to do it with.

## **NUCO Research and Development**

Innovation is important to the success of any company. Our team of chemists, researchers and developers are constantly looking to develop innovative products that will help our customers solidify their positions in their respective markets and industries. An enormous amount of time is also spent on furthering the development of our current products and ensuring they meet and exceed your expectations.

## **NUCO Distribution Channel**

Through strategic distribution channels, NUCO supplies Residential, Commercial, Industrial, Electrical, Mechanical, Marine, OEM, and Transportation markets. This business is distributed throughout Canada, the United States, Europe and South America.

## Firestop Technical Services

NUCO Inc. provides technical support services tailored to the needs of any project. We work in partnership with specifiers to build strong project submittals; With our distributors to provide accurate take-off estimations; with end-users to provide guidance, support, or troubleshooting; and any other needs our customers might have. NUCO will support our customers throughout the full lifecycle of their projects.

### *Specific Firestop Submittal Packages:*

In many cases building a strong submittal for your firestopping project is the key to success. We work alongside our customers to select the best and most cost-effective firestop systems for any project. We also build a specification submittal package that includes all the documentation needed for specifiers, architects, installers, and inspectors. In addition, our online firestop system selection tool and submittal generator are available 24/7 on our website.

### *Engineering Judgements:*

When no certified firestop system exists for a through-penetration, joint, or curtain wall fire separation; NUCO's technical support team can tailor a construction solution for your needs. Our team will review the scenario, propose a solution, and create a custom engineering evaluation detail to suit the needs of the project and building code with a strong emphasis on life safety.

## AMAZING PRODUCTION CAPABILITIES



Guelph ON Facility



Incredibly Efficient Processes



Visit [www.NUCOInc.com](http://www.NUCOInc.com) for our plant tour video.

# ACETOXY 100% Silicone Sealants

## ■ NUFLEX® 302 GENERAL PURPOSE SILICONE SEALANT



### Features:

- 100% Silicone
- NuFlex® 302 is Certified by NSF to Standard 51
- Water resistant before, during, and after curing
- RTV (Room Temperature Vulcanization)
- Excellent extreme temperature performance
- 50 year durability
- Can be applied in sub-zero temperatures
- NuFlex® 302 General Purpose has achieved GREENGUARD GOLD Certification

### Basic uses include caulking and sealing around:

1. Form-in place gaskets with no oil contact
2. Duct joints
3. Areas that need weather stripping
4. Sinks, basins, showers, and tubs

### Bonds To:

- Metal
- Laminates
- Glass
- Wood
- Silicone resin and vulcanized silicone
- Ceramic
- Natural & synthetic fibres
- Painted surfaces
- Most plastics



SKU	Colour	Size
30280	Clear	83 mL
30281	White	83 mL
30283	Black	83 mL
30200	Clear	300 mL
30201	White	300 mL
30208	Translucent	300 mL
30202	Aluminium	300 mL
30203	Black	300 mL
30204	Bronze	300 mL
30205	Almond	300 mL
30206	Grey	300 mL
30207	Brown	300 mL

## ■ NUFLEX® 302 BATH & KITCHEN SILICONE SEALANT



### Features:

- 100% Silicone & mildew resistant
- NuFlex® 302 is Certified by NSF to Standard 51
- Water resistant before, during, and after cure
- RTV (Room Temperature Vulcanization)
- Excellent extreme temperature performance
- 50 year durability
- Can be applied in sub-zero temperatures
- NuFlex® 302 Bath & Kitchen has achieved GREENGUARD GOLD Certification

### Basic uses include caulking and sealing around:

1. Bathtubs
2. Shower stalls
3. Bathroom vanities
4. Kitchen counters and sinks

### Bonds To:

- Metal
- Laminates
- Glass
- Wood
- Silicone resin and vulcanized silicone
- Ceramic
- Natural & synthetic fibres
- Painted surfaces
- Most plastics

### Other uses include:

1. Replacing ceramic tiles
2. Gasket making for dishwasher doors
3. Sealing inside refrigerators and freezers



SKU	Colour	Size
30240	Clear	300 mL
30241	White	300 mL
30248	Translucent	300 mL
30245	Almond	300 mL
30246	Grey	300 mL
30251	Bone	300 mL



## ■ NUFLEX® 302 HIGH TEMPERATURE SILICONE SEALANT



### Features:

- 100% Silicone
- NuFlex® 302 is Certified by NSF to Standard 51
- Water resistant before, during, and after curing
- RTV (Room Temperature Vulcanization)
- Adheres to many substrates
- Excellent extreme temperature performance
- 50 year durability
- Can be applied in sub-zero temperatures
- Withstands up to 316 °C (600 °F)

### Basic uses include caulking and sealing around:

1. Form-in place gaskets where there is no oil contact
2. Sealing and encapsulating heating elements in appliances
3. Moving oven belts
4. Industrial ovens and bag filters on smoke stacks

### Bonds To:

- Metal
- Laminates
- Glass
- Wood
- Silicone resin and vulcanized silicone
- Ceramic
- Natural & synthetic fibres
- Painted surfaces
- Most plastics

### Other uses include:

1. General repairs on a variety of substrates
2. Critical bonding, sealing, potting, encapsulating and protective coatings where parts must preform at high temperatures



SKU	Colour	Size
30289	Red	83 mL
30293	Black	83 mL
30209	Red	300 mL
30213	Black	300 mL

■ **NUFLEX<sup>®</sup> 333 AQUARIUM SILICONE SEALANT**




**Features:**

- 100% silicone with 50 year durability
- Water resistant before, during, and after curing
- RTV (Room Temperature Vulcanization)
- Strong adhesion to glass
- For aquariums up to 400 litres (100 US gallons)
- Eliminates toxic poisoning of fish and plants which is common with metal frames & tanks made with toxic glues
- Does not shrink, dry out or crack

**Use:**

- Construction and sealing of aquariums

SKU	Colour	Size
33300	Clear	300 mL



■ **NUFLEX<sup>®</sup> 366 MARINE SILICONE SEALANT**



**Features:**

- 100% Silicone
- Water resistant before, during, and after curing
- RTV (Room Temperature Vulcanization)
- Adheres to many substrates
- Ideal for above water line marine applications
- Resists extreme weather, vibration, moisture, and weathering
- 50 year durability
- Can be applied in sub-zero temperatures

**Bonds To:**

- Fibreglass
- Most plastics
- Metal
- Laminates
- Glass
- Wood
- Silicone resin and vulcanized silicone rubber
- Ceramic
- Painted surfaces

SKU	Colour	Size
36600	Clear	300 mL
36601	White	300 mL

**Basic uses include caulking and sealing around:**

1. Portlight windows
2. Inspection hatches
3. Doors
4. Areas that need weather-stripping

**Other uses include:**

1. General repairs on a variety of substrates
2. Non load-bearing bonding
3. Gasket replacements



**ACETOXY SILICONE QUICK FACTS**

THE GOLD STANDARD FOR TYPICAL SEALING NEEDS

**QUICK CURING**

Acetoxy silicones cure rapidly, often within hours, making them ideal for fast-paced projects.

**DURABILITY**


Resistant to weathering, UV radiation, and extreme temperatures, ensuring long-lasting seals.

**STRONG ADHESION**

Provides excellent adhesion to non-porous surfaces such as glass, metal, and ceramics.

**APPLICATIONS**

Perfect for kitchens, bathrooms, and other high-moisture environments due to their mold and mildew resistance.



# NEUTRAL CURE 100% Silicone Sealants

## ■ NUFLEX® 309 METAL & VINYL SILICONE SEALANT



### Features:

- 100% Silicone
- Water resistant before, during, and after cure
- RTV (Room Temperature Vulcanization)
- Excellent adhesion to both porous and non-porous substrates
- 50 year durability
- Low odour
- Non-sag / non-slumping

### Basic uses include:

1. Exterior weather proofing
2. Sealing construction joints
3. Sealing metal and vinyl siding

### Bonds To:

- Galvanized steel
- Aluminium
- Steel
- Vinyl
- Most plastics
- Masonry, stone, & concrete
- Ceramics
- PVC

### Other uses include:

1. Bonding curtain wall joints
2. Mullion joints
3. OEM manufacturing



SKU	Colour	Size
30906	Grey	300 mL



## ■ NUFLEX® 313 FAST CURE GLASS & VINYL SILICONE SEALANT



### Features:

- 100% Silicone
- Water resistant before, during, and after cure
- RTV (Room Temperature Vulcanization)
- Accelerated cure time
- Adheres to many porous substrates
- 50 year durability

### Basic uses include:

1. OEM manufacturing (truck & trailer bodies)
2. Cap, heel, & toe beads for window sealing

### Bonds To:

- Aluminium
- Wood
- Galvanized steel
- Glass
- Most metals
- Most plastics
- Most vinyls

### Other uses include:

1. Appliance repair, reassembly, and reconditioning
2. Sealing vinyl components where speed is important

SKU	Colour	Size
31300	Clear	300 mL
31301	White	300 mL

## ■ NUFLEX® 319 GLAZING SILICONE SEALANT



### Features:

- 100% Silicone
- Water resistant before, during, and after cure
- RTV (Room Temperature Vulcanization)
- NuFlex® 319 Glazing has achieved GREENGUARD GOLD Certification
- An excellent multi-purpose neutral cure
- Adheres to many porous substrates
- 50 year durability
- Can be applied in sub-zero temperatures
- Meets AAMA

### Basic uses include:

1. Exterior weather proofing
2. Sealing joints where one or more substrate is stone
3. Cap, heel, & toe beads for window glazing

### Bonds To:

- Glass
- Plastic
- Metal
- Concrete
- Masonry
- Stone
- PVC
- Ceramic

### Other uses include:

1. Replacing glass tiles & back splashes
2. Gasket making for appliances
3. Sealing PVC door tracks to the ground



SKU	Colour	Size
31900	Clear	300 mL
31901	White	300 mL

## ■ NUFLEX® 311 SELF-LEVELING SILICONE JOINT SEALANT



### Features:

- Self-leveling
- 100% Silicone
- Water resistant before, during, and after cure
- NuFlex® 311 Joint Sealant has achieved GREENGUARD GOLD Certification
- RTV (Room Temperature Vulcanization)
- Excellent adhesion
- Low odour

### Basic uses include:

1. Non structural expansion joints
2. Horizontal joints in concrete and cementitious substrates

### Bonds To:

- Ceramic
- Aluminium
- Concrete
- Vinyl
- Wood
- Most construction substrates

### Other uses include:

1. Control joints in parking garages, driveways, swimming pool decks, concrete floors, sidewalks and foundations



SKU	Colour	Size
31106*	Limestone	300 mL

\*Special order

## ■ NUFLEX® 311 RV FORMULATION SILICONE JOINT SEALANT



### Features:

- Self-leveling
- 100% Silicone
- Water resistant before, during, and after cure
- NuFlex® 311 RV Joint Sealant has achieved GREENGUARD GOLD Certification
- RTV (Room Temperature Vulcanization)
- Excellent adhesion
- Low odour

### Basic uses include:

1. Seal around penetrating items on the RV roofs
2. Basic roof repairs

### Bonds To:

- Ceramic
- Aluminium
- Concrete
- Vinyl
- Wood
- Many TPO and EDPM roof materials (pre-test for adhesion)

### Other uses include:

1. Horizontal sealing on bus, truck, van, and trailer applications



SKU	Colour	Size
31111	RV White	300 mL

## ■ NUFLEX® 331 EXTERIOR SIDING & TRIM SILICONE SEALANT



### Features:

- 100% Silicone
- Water resistant before, during, and after cure
- RTV (Room Temperature Vulcanization)
- NuFlex® 331 Siding & Trim has achieved GREENGUARD GOLD Certification
- Ideal for most exterior trim and siding
- Adheres to many porous and non-porous substrates
- 50 year durability
- Can be applied in sub-zero temperatures
- Meets AAMA

### Bonds To:

- PVC
- Most plastics
- Wood
- Vinyl
- Most metals (including aluminium)

### Basic uses include:

1. Exterior weather proofing
2. Sealing joints between window frames and siding
3. Adhering trim and siding



SKU	Colour	Size
33100	Clear	300 mL

## NEUTRAL CURE SILICONE QUICK FACTS

THE VERSATILE SOLUTION FOR A WIDE RANGE OF APPLICATIONS

### NON-CORROSIVE

Neutral cure silicones do not release acidic by-products during curing, making them safe for use on all metals and other sensitive materials.

### FLEXIBILITY

Maintains flexibility over time, accommodating movement in joints and ensuring lasting performance even in dynamic environments.

### WEATHER RESISTANCE

Waterproof and offering excellent resistance to UV radiation, ozone, and extreme temperatures.

### VERSATILE APPLICATIONS

Compatible with various substrates like glass, metal, wood, and plastics, suitable for construction and industrial uses.

# SPECIALTY Sealants

## ■ NUFLEX® 635 HYBRID<sup>SP</sup> SPECIALTY SEALANT



### Features:

- Class 35 sealant
- Specialty hybrid formulation for high performance applications
- UV stable
- NuFlex® 635 has achieved GREENGUARD GOLD Certification
- Excellent exterior weathering resistance
- Low VOC
- Non-corrosive
- Paintable

### Basic uses include caulking and sealing around:

1. Interior and exterior joining and sealing
2. Perimeter sealing of openings and joints
3. EIFD, Aluminium, masonry, and vinyl siding
4. Low traffic expansion joint sealing

### Bonds To:

- Waterproof membranes & shower systems
- Cementitious board & panels
- Wood (including treated wood)
- Glass
- Metals
- Plastics, including PVC
- Vinyl\* *test for suitability prior to full production*
- EPS & EXP foam

### Other uses include:

1. Bonding and joint sealing in automotive and OEM
2. Bonding and sealing where UV stability is required
3. Sanitary applications
4. Expansion and control joints



SKU	Colour	Size
63501	White	296 mL

## ■ NUFLEX® 110 BUTYL ROOFING SEALANT



### Features:

- Skinning rubber butyl
- Ideal exterior weathering sealant
- Exterior & interior use
- Paintable
- Adheres to many dissimilar substrates
- Will not crack
- Resistant to sunlight, ozone, water, vapour transmission, cleaning chemicals, and weathering

### Basic uses include:

1. Gutter down spouts
2. Metal storm windows
3. Doors & lap joints

### Bonds To:

- Metal (including aluminium)
- Glass
- Wood
- Brick
- Stone
- Masonry
- Paint

### Other uses include:

4. Sealing under shower door tracks or metal thresholds & other exterior building materials
5. Sealing narrow seams

SKU	Colour	Size
11001	White	300 mL
11003	Black	300 mL
11006	Grey	300 mL

## ■ NUFLEX® 650 FLEXONE POLYURETHANE SEALANT/ADHESIVE



### Features:

- 100% polyurethane
- Joint movement capability of  $\pm 35\%$
- Water immisible
- Can be applied above & below grade
- Low VOC
- Weather resistant
- Excellent adhesion to most common substrates
- Creates permanent seal

### Basic uses include:

1. Sealing expansion joints
2. Adhering blocks and bricks
3. Sealing above and below grade penetrations in unrated construction

### Bonds To:

- Stone
- Concrete
- Masonry
- Wood
- Metal (including aluminium)
- Painted surfaces
- Clay
- Vinyl

### Other uses include:

1. General repairs
2. Sealing areas with constant water immersion

SKU	Colour	Size
65006	Grey	296 mL
65056	Grey	591 mL



# PAINTABLE Sealants



## ■ NUFLEX® 130 ACRYLIC PAINTER'S CAULK / TRIM SEAL



### Features:

- Paintable
- Easy clean-up (with water)
- Matte finish
- Interior & exterior use
- Mildew resistant once cured

### Basic uses include:

1. All-purpose sealant for cracks and joints and exhibits good adhesion to a full range of construction substrates

**NOTE:** Must be painted or covered once cured.

### Bonds To:

- Wood
- Concrete
- Metal
- Tile
- Masonry (including brick)

SKU	Colour	Size
13001	White	300 mL



## ■ NUFLEX® 180 SILICONIZED ACRYLIC



### Features:

- Paintable
- Flexible
- Siliconized
- Easy clean-up (with water)
- Gloss finish
- Interior & exterior use
- Mildew resistant once cured

### Basic uses include:

1. All-purpose sealant for cracks and joints and exhibits good adhesion to a full range of construction substrates

### Bonds To:

- Masonry, concrete, brick
- Porcelain
- Ceramic tile
- Glass
- Wood
- Metal
- Marble

### Other uses include:

1. It is also recommended for sealing interior joints between walls and panels, around door frames and baseboards and joints between bathroom fixtures and walls.

SKU	Colour	Size
18000	Clear	300 mL
18001	White	300 mL

## ■ NUFLEX® CAULKING GUNS / DISPENSERS

	SKU	Product Name	Description
A	CG000113	NuFlex 113	Fits up to 310 ml cartridge
B	CG000138	NuFlex 138	Fits up to 310 ml cartridge
C	CG000128	NuFlex 128	Fits up to 850 ml cartridge
D	CG 620-AL	NuFlex 620 AL Sausage Gun	Fits up to 850 ml sausage
E	CGDL45T13	NuFlex Bulk Gun	Fits up to 850 ml of bulk product



# Do you know what's in your silicone?

## NUFLEX SILICONE PRODUCTS ARE ALWAYS 100% SILICONE

NuFlex Silicone products are 100% pure silicone, offering superior performance and durability, with no added solvents or fillers that can compromise quality.



# CONSTRUCTION Adhesives

## ■ NUFLEX® 435 WATERTIGHT HYBRID ADHESIVE



**Features:**

- High initial tack
- Permanently flexible
- 100% watertight
- Non-solvent based / non-corrosive
- Low VOC / no odour
- NuFlex® 435 has achieved GREENGUARD GOLD Certification

**Bonds To:**

- Cove bases
- Cementitious board
- Flooring
- Stair treads & nosings
- Wood (including treated wood)
- Plastics, including PVC and Vinyl
- Metals (including galvanized steel)
- EPS and XPS foam

**Basic uses include:**

1. Creating a strong, flexible, watertight bond
2. Adhering cementitious substrates where flexibility is valued
3. Large panel bonding such as: cultured marble slabs, waterproof building boards for showers, etc.



SKU	Size	Theoretical Yield:
43500	296 mL	9.1 meters (30 linear feet)

## ■ NUFLEX® 446 ACOUSTICAL VAPOUR BARRIER ADHESIVE



**Features:**

- Non-skinning
- Non-curing
- Non-hardening
- Permanently flexible
- Outstanding adhesion to many substrates

**Bonds To:**

- Polyethylene vapour barrier
- Wood
- Metal

**Basic uses include:**

1. Perimeter sealing polyethylene vapour barrier over fiberglass batt or other insulations
2. Metal roof panel rib sealant
3. Bedding sealant



SKU	Size	Theoretical Yield:
44600	296 mL	9.1 meters (30 linear feet)
44680	828 mL	26.2 meters (86 linear feet)

## ■ NUFLEX® 456 HEAVY DUTY CONSTRUCTION ADHESIVE



**Features:**

- VOC compliant
- Superior adhesion strength
- Remains flexible
- Exceeds AFG-01 specification
- Freeze-thaw stable
- Superior extreme temperature adhesion
- Adheres to many substrates

**Bonds To:**

- Wood (dry, wet, or frozen)
- Metal
- Brick
- Concrete
- Ceramics

**Basic uses include:**

1. Adhering large panel-type substrates to most common construction materials.
2. Reducing floor squeaks by using as a subfloor adhesive



SKU	Size	Theoretical Yield:
45600	296 mL	9.1 meters (30 linear feet)
45680	828 mL	26.2 meters (86 linear feet)

# EPOXY Putty Sticks

**Features:**

- Easy to use
- Superior adhesion strength
- Many uses
- Compact design
- Extra long shelf life
- Adheres to many substrates

**Bonds To:**

- See TDS for specific substrate information

SKU	Description	Size	Pack
450670-24	RepairitQuik	3.5"	24
450555-24		7.0"	
451070-24	FastSteel	3.5"	24
451065-24		7.0"	
457070-24	QuikAluminium	3.5"	24
457080-24		7.0"	
462570-24	QuikCopper	3.5"	24
462550-24		7.0"	
470570-24	Aquamend	3.5"	24
470880-24		7.0"	
471070-24	QuikWood	3.5"	24
471080-24		7.0"	
475570-24	QuikPlastic	3.5"	24
475560-24		7.0"	
477570-24	InstaCrete	3.5"	24
477680-24		7.0"	
600478070-24	QuikTitanium - Hi Temp.	3.5"	24
600478055-24		7.0"	



## ■ NUFLEX® 458 SUBFLOOR CONSTRUCTION ADHESIVE



### Features:

- Superior adhesion strength
- Freeze-thaw stable
- AFG-01 approved
- Superior extreme temperature adhesion
- Remains permanently flexible
- Versatile
- Waterproof

### Basic uses include:

1. Adhering subfloor panels in interior and exterior installations (with the aide of mechanical fasteners)

### Bonds To:

- Plywood
- Particleboard
- OSB
- Wet, dry, frozen ACA & CCA treated lumber
- Masonry
- Concrete
- Brick
- Ceramic
- Slate

SKU	Size	Theoretical Yield:
45880	828 mL	26.2 meters (86 linear feet)

## ■ NUFLEX® 480 PREMIUM POLYURETHANE CONSTRUCTION ADHESIVE



### Features:

- VOC compliant
- Rigid, non-flexible when cured
- Superior adhesion strength
- Non-freezing & waterproof
- AFG-01 approved
- Low odour
- Versatile

### Basic uses include:

1. Adhering most construction substrates to form a watertight bond.
2. Bonding where extra strength is needed

### Bonds To:

- Wood (dry, wet, or frozen)
- Metal
- Brick
- Concrete
- Ceramics
- Stone (marble, slate, etc.)
- Some mirrors (must be mechanically fastened)
- Most foam insulations:
  - EPS (Expanded Polystyrene Foam)
  - XPS (Extruded Polystyrene Foam)
  - Polyisocyanurate

SKU	Size	Theoretical Yield:
48000	296 mL	9.1 meters (30 linear feet)
48080	828 mL	26.2 meters (86 linear feet)



# OUR FIRST HYBRID PRODUCT LINE

## SEALANTS & ADHESIVES



### NEW ADHESIVE TECHNOLOGY

#### 435 WATERTIGHT HYBRID ADHESIVE:

- COVE BASES
- CEMENTITIOUS BOARDS & PANELS
- WOOD, VINYL, AND LAMINATE FLOORING
- STAIR TREADS AND NOSINGS
- GLASS AND MIRRORS
- PLASTICS, INCLUDING PVC AND VINYL
- EPS AND XPS FOAM
- AND MUCH MORE

### NEW SEALANT TECHNOLOGY

#### 635 HYBRIDSP<sup>®</sup> SPECIALTY SEALANT:

- WATERPROOF MEMBRANES & SHOWER SYSTEMS
- SEALING PIPE & FIXTURE PENETRATIONS IN SHOWERS
- CEMENTITIOUS BOARDS & PANELS
- MIRRORS
- VINYL
- PLASTICS, INCLUDING PVC
- AND MUCH MORE

# SINGLE COMPONENT PU Foams

## ■ ULTRASEAL® PF-100/PF-50 EXTREME ALL-WEATHER POLYURETHANE FOAM



### Features:

- All-Weather performance (down to -18°C)
- Excellent bead control
- Helps save energy costs by stopping air flow
- Low expansion
- UltraSeal® PF-100 & PF-50 has achieved GREENGUARD GOLD Certification

### Basic uses include:

1. Sealing around windows & doors
2. General gap, crack, and crevice filling/sealing
3. Sealing unrated pipe & duct penetrations



SKU	Format	Size	R-Factor (aged)
71600	Gun	660 mL (24 oz.)	4-5 per inch
70300	Straw	330 mL (12 oz.)	4-5 per inch
70600	Straw	660 mL (24 oz.)	4-5 per inch

## ■ ULTRASEAL® PF-140 BLACK GUN FOAM



### Features:

- Easily concealed
- Stops transfer of water & unwanted elements
- Black in colour
- Paintable
- Low expansion

### Basic uses include:

1. Sealing around windows & doors
2. General gap, crack, and crevice filling/sealing
3. Sealing unrated pipe & duct penetrations



SKU	Size	R-Factor (aged)
71603	660 mL (24 oz.)	4-5 per inch

## ■ PERFECTSEAL® GUN FOAM



### Features:

- O-zone friendly
- Low expansion
- Economically priced
- Foam is green in colour

### Basic uses include:

1. Sealing around windows & doors
2. General gap, crack, and crevice filling/sealing
3. Sealing unrated pipe & duct penetrations

SKU	Size
51900	800 mL (29 oz.)

## ■ IPF GREEN GUN FOAM



### Features:

- Low expansion formula
- Constant application pressure
- Repels insects
- Longer shelf life (18 months)
- Achieves GREENGUARD GOLD Certification
- Contains natural ingredients for insect repellence



### Basic uses include:

1. Sealing around windows & doors
2. General gap, crack, and crevice filling/sealing
3. Sealing unrated pipe & duct penetrations

SKU	Size	R-Factor (aged)
72900	750 mL (29 oz.)	4-5 per inch

## ■ IPF ALLWEATHER PRO GUN FOAM



### Features:

- All-weather performance (down to -10°C)
- Low expansion formula
- Helps save energy costs by stopping airflow
- Achieves GREENGUARD GOLD Certification
- Low expansion, high yield product
- Fine cell structure reduces waste

### Basic uses include:

1. Sealing around windows & doors
2. General gap, crack, and crevice filling/sealing
3. Sealing unrated pipe & duct penetrations

SKU	Size	R-Factor (aged)
72400	660 mL (24 oz.)	4-5 per inch

## ■ 2SPEC SPECIALTY GUN FOAM




### Features:

- Dark grey foam colour
- Optimal performance in winter conditions
- Suitable for sealing joints, penetrations, and general insulation tasks
- Compatible with standard professional foam dispensers
- Excellent results from -10 up to +30°C

### Basic uses include:

1. Sealing around windows & doors
2. General gap, crack, and crevice filling/sealing
3. Sealing unrated pipe & duct penetrations



SKU	Size	R-Factor (aged)
51903	750 mL (29 oz.)	4-5 per inch

# TWO COMPONENT PU Foams & Accessories

# ULTRASEAL<sup>®</sup> PU FOAMS

## ■ ULTRASEAL<sup>®</sup> PF-200/600 2-COMPONENT FOAM SYSTEMS, E-84 CLASS 1

### Features:

- UltraSeal<sup>®</sup> PF-200/600 has achieved GREENGUARD GOLD Certification
- All weather performance
- Quick curing
- Portable
- High density polyurethane
- Repeated use

### Uses:

- Residential & industrial construction
- Cold storage
- Truck trailer
- Mobile home
- Restoration & renovation
- Garage
- Metal structures
- Marine & flotation
- Asbestos abatement



SKU	Description	Size
72002	All-in-one kit	200 bd.ft
76002	All-in-one kit	600 bd.ft
76022	Tanks only	600 bd.ft



## Single Component Foam Accessories

*"Enhance your foam performance with reliable and easy-to-use accessories."*

### G1 Foam Gun

SKU	Description
G1	Our best foam gun

#### Features:

- Semi-steel construction
- Foam control dial
- Ergonomically correct
- The professional's choice
- Long lasting
- Swiss made



### G2 Foam Gun

SKU	Description
G2	Great quality foam gun

#### Features:

- Semi-steel construction
- Foam control dial
- Economical
- Ergonomically correct
- The professional's choice
- Long lasting



### PF-10 Gun Foam Cleaner

SKU	Size
73400	330 mL (12 oz.)

#### Features:

- Dissolves uncured foam
- Ideal for gun maintenance



### PF Optimizer

SKU	Description
G-123	75 per pack


#### Features:

- Accelerator tip that maximizes yield
- Easily attaches to end of foam gun
- Optimizes cell structure



## Two Component Foam Accessories

*"Two component foam accessories to get you shooting in the right direction!"*



### Fan tip nozzle:

- Wide vertical spray pattern for large area coverage
- Improved uniformity and surface appearance
- Clear and solvent cleanable
- Speeds application and productivity



### Cone tip nozzle:

- Conical spray pattern
- Directed, high-velocity flow
- Clear and solvent cleanable
- Easily adapted for pour-in-place application



### Nozzles & Hoses

SKU	Description
76025	Colorwise Snap-Tip Nozzles - 25 pcs
70015	PF-600 15' Hose
70016	PF-600 25' Hose

# 100% SILICONE Firestop Sealants

## ■ SELF-SEAL® SL-100 SELF-LEVELLING SILICONE FIRESTOP SEALANT

### Features:

- Self-leveling
- 100% silicone
- Water-resistant before, during and after cure
- Self-Seal® SL-100 has achieved GREENGUARD GOLD Certification



SKU	Colour	Size	
10036	Limestone	300 mL	Cartridge
10086	Limestone	850 mL	Cartridge
10056	Limestone	591 mL	Sausage
10050	Yellow	591 mL	Sausage
10016	Limestone	10 L	Pail
10076	Limestone	17 L	Pail
10070	Yellow	17 L	Pail



## ■ SELF-SEAL® GG-200 GUN GRADE SILICONE FIRESTOP SEALANT

### Features:

- Non-sag
- 100% silicone
- Water-resistant before, during and after cure
- Self-Seal® GG-200 has achieved GREENGUARD GOLD Certification



SKU	Colour	Size	
20036	Limestone	300 ml	Cartridge
20039	Red	300 ml	Cartridge
20086	Limestone	850 ml	Cartridge
20089	Red	850 ml	Cartridge
20056	Limestone	591 ml	Sausage
20059	Red	591 ml	Sausage
20016	Limestone	10 L	Pail
20076	Limestone	17 L	Pail




## ■ SELF-SEAL® GG-266 INTUMESCENT SILICONE FIRESTOP SEALANT

### Features:

- Intumescent: expands at temps over 150°C, (300°F) to close gap left by combustible pipe
- Non-sag
- 100% silicone
- Water-resistant before, during and after cure
- Self-Seal® GG-266 has achieved GREENGUARD GOLD Certification



SKU	Colour	Size	
26639	Red	300 ml	Cartridge
26659	Red	591 ml	Sausage
26619	Red	10 L	Pail



## Looking for a listing?

It's as easy as 1... 2... 3...!

Visit [www.FindAListing.com](http://www.FindAListing.com)

1. Select the Building Type under the classification you require.
2. Use the Easy-to-Use chart to find the right listing.
3. Click on the listing number ... the listing PDF will pop up!

[www.NUCOINC.COM](http://www.NUCOINC.COM)



GENERATE SUBMITTALS

Once you have filtered and selected the appropriate systems, you may generate a submittal. Click [Fill out your information](#) to input your information (this is helpful if you need assistance down the road). Lastly, click [Get your submittal](#) to generate a downloadable PDF of your submittal.



RESPONSIVE & MOBILE FRIENDLY

[www.NUCOInc.com](http://www.NUCOInc.com) is a fully responsive website that works on all devices. It is built on an efficient framework to ensure that it saves you time (and data charges!). It is optimized for your device, whether it's an iPhone, Android phone, tablet, or a desktop or laptop computer.



BROWSE SYSTEMS

Each system features an assembly summary, a list of relevant products, any particular details in the drawing, and a link to view/download the listing itself. You may click "Add to submittal" if you are generating a submittal.

## ■ SELF-SEAL® TYPE-SSC INTUMESCENT COLLARS

**Features:**

- Expands to form a pressure tight seal which is resistant to water, smoke and toxic gases
- Low profile
- Pre-fabricated
- Ideal for tight spaces and angles



SKU	Size	Pack
25015	1.5"	10
25020	2.0"	10
25030	3.0"	10
25040	4.0"	10
25060	6.0"	1

## ■ SELF-SEAL® INTUMESCENT FIREBANDS

**Features:**

- Expands to form a pressure tight seal which is resistant to water, smoke and toxic gases
- Pre-formed and low profile
- Held tightly around pipe with the adhesive strip attached to the fireband
- Easy to install




SKU	Size	Pack
24015	1.5"	10
24020	2.0"	10
24030	3.0"	10

## ■ SELF-SEAL® OBG-700 OUTLET BOX GASKETS

**Features:**

- Expands to form a tight seal
- Perfect for both metal and plastic electrical boxes
- Saves money and time
- Excellent for retrofit and new construction
- A great selling feature for home developers

SKU	Description	Pack
70011	Single Switch	50
70012	Double Switch	50
70021	Single Receptacle	50
70022	Double Receptacle	50
70031	Single Decor	50
70032	Double Decor	50
70055	Stove & Dryer Receptacle	50
70056	Light Fixture Receptacle	50



## ■ SELF-SEAL® MW-300 MINERAL WOOL

**Features:**

- Pre-cut strips for easy installation
- Excellent sound deadening and insulation value
- 4.5 pcf (72kg/m<sup>3</sup>) density



SKU	Description	Size	Linear Feet
30024	4' lengths - 25 lbs	2" x 4"	96
30034	4' lengths - 25 lbs	3" x 4"	72
30044	4' lengths - 25 lbs	4" x 4"	48

## ■ SELF-SEAL® SYSTEM IDENTIFICATION LABELS

**Features:**

- Pre-cut labels for ease of use
- Intended to be a permanent use label
- Easy to fill out
- Can be used for any Self-Seal firestop listing



Please contact your sales rep for ordering info or give us a call at 1-800-853-3984.



FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology. The FBC System Compatible Logo, FBC™, FlowGuard Gold®, BlazeMaster®, Corzan®, and TempRite® are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates.

**NuFlex**<sup>®</sup>  
SEALANTS

**ULTRASEAL**<sup>®</sup>  
PU FOAMS

**SELF-SEAL**<sup>®</sup>  
FIRESTOPPING PRODUCTS



1-800-853-3984

[www.NUCOInc.com](http://www.NUCOInc.com)

Visit us on [Facebook](#), [Twitter](#) & [Instagram](#)!

150 Curtis Drive  
Guelph, ON N1K 1N5  
519-823-4994

**QUALITY. PERFORMANCE. DEPENDABILITY. STRENGTH.**