



STRATA_HEAT™ Mat

DS-26.1-0126

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

STRATA_HEAT™ Mat

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: laticrete.com

3. PRODUCT DESCRIPTION

STRATA_HEAT Mat combines the comfort of floor heating wire with the advantages associated with STRATA_MAT™ uncoupling membrane. Warm your tile floor and enhance the mechanical bond to the substrate. STRATA_HEAT Mat will provide faster drying of the mortar, allowing for shorter time to grout. At the same time it will easily hold the STRATA_HEAT Wire at multiple spacing scenarios for floor heating or warming installations. Just as our other uncoupling membranes it is specifically designed for use with both modified and unmodified mortars, you can use the appropriate mortar for the installation.

Uses

- Doubles as an uncoupling mat and holder for STRATA_HEAT Wire

Advantages

- Use with STRATA_HEAT Wire and STRATA_HEAT Thermostat to provide luxury and comfort to your room

- Multiple spacing options allow for variability in Heat output
- Mortar Hydration Vents - creates a mechanical bond between the mat and adhesive mortar - allows the mortar to cure faster providing a stronger bond of tile for faster time to grout
- Allows for use of the appropriate mortar per industry standards
- Provides vapor management
- Instant coverage verification - allows for installer to see mortar coverage underneath the mat during installation without having to lift and verify
- Allows for easier floor layout as chalk lines are easily visible on surface prior to tile installation
- Part of the LATICRETE® Lifetime System Warranty

Suitable Substrates (Interior Use Only)

- Cement Backer Board
- Cement Terrazzo
- Concrete
- Existing Ceramic Tile and Stone
- Gypsum Underlayment Or Light Weight Concrete
- Mortar Bed
- Oriented Strand Board (OSB)
- Oriented Strand Board (OSB)
- Resilient Flooring
- Exterior Glue Plywood (Interior Only)

Approximate Coverage

- 161 ft² roll- 39" x 49' 6" (15 m² - 1m x 15m)
- 10 x 8.6 ft² sheets – 39" x 31" (0.79 m² - 1m x 0.79m)

Shelf Life

Unlimited. Store at 40°F to 75°F (4°-24°C) in a covered area (out of the sun).

Limitations

- Interior floor installations over suitable substrates only.
- DO NOT bond to particle board, hardwood surfaces, luan or sponge backed vinyl flooring.
- Not for use over expansion joints or structural movement cracks.
- STRATA_HEAT™ is not intended for use as a waterproofing membrane.
- Not for use as a wear surface, must be covered with tile.

- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE® Waterproofing Membrane (see Section 10 FILING SYSTEMS).
- Minimum of 3.5" x 3.5" (89 mm x 89 mm) ceramic, porcelain or glass tile and stone can be set over STRATA_HEAT.
- Do not leave STRATA_HEAT exposed for more than one week. Cover the STRATA_HEAT after installing it and protect it from other trades if not setting tile immediately. If the STRATA_HEAT is going to be left for more than 72 hours it should be covered with thin-set and troweled smooth covering the STRATA_HEAT completely to protect it from potential UV damage and physical abuse.
- Note: Surfaces must be structurally sound, stable and rigid enough to support ceramic/stone tile, thin brick and similar finishes. Substrate deflection under all live, dead and impact loads, including concentrated loads, must not exceed L/360 for thin bed ceramic tile/brick installations or L/480 for thin bed stone installations where L=span length.
- When used with LATICRETE self-leveling underlayments; consult the respective LATICRETE Product Data Sheets for specific installation instructions.

Cautions

- During cold weather, protect finished work from traffic until fully cured
- For green marble, resin backed or other moisture sensitive tile or stone, use LATAPOXY® 300 Adhesive, refer to Data Sheet 633.0
- Suitable for interior non-industrial vehicular traffic applications over concrete substrates when using 254 Platinum to adhere STRATA_HEAT™ to the concrete and to install tiles over the STRATA_HEAT following a 7 day cure @ 70°F (21°C)
- For white and light-colored marbles use a white LATICRETE mortar
- Do not turn STRATA_HEAT Wire on until entire installation of tile and grout has cured for a minimum of 7 days at 70°F (21°C)
- Do not hook wire up to power while still on the spool
- Protect finished work from traffic until fully cured
- Use only appropriate size of STRATA_HEAT Wire for specified area of floor to be heated. DO NOT TUCK/INSTALL/FOLD EXCESS WIRE INTO WALL CAVITY
- Do not store outside exposed to sunlight (UV light)
- Carefully read this installation manual before commencing installation

4. TECHNICAL DATA

Applicable Standard

- ASTM C627
- ANSI A118.12

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Surface Preparation

Concrete Substrates

Concrete must be cured sufficiently to support tile installation traffic as determined by design professional, construction manager, or general contractor. The surface shall be free of voids, sharp protrusions and loose aggregate. All surfaces should be between 40°F (4°C) and 90°F (32°C) and structurally sound, clean and free from all dirt, oil, grease, paint, concrete sealers or curing compounds and cement laitance. Rough or uneven concrete surfaces should be made smooth with a LATICRETE Latex Portland cement underlayment to provide a wood float or better finish. Do not level with gypsum or asphalt based products.

OSB or Exterior Glue Plywood Substrates

Refer to LATICRETE Technical Data Sheet 152 "Bonding Ceramic Tile, Stone or Brick Over Wood Floors" (refer to section 10, FILING SYSTEMS).

1. Installer must verify that deflection under all live, dead and impact loads of interior plywood floors does not exceed industry standards of L/360 for ceramic tile and brick or L/480 for stone installations where L span length.
 2. Minimum construction for interior ceramic or porcelain tiled floors as follows:
 - For single layer plywood or OSB – 16" (406 mm) o.c. joist spacing – use 5/8" (15 mm) tongue and groove nominal thickness.
 - For single layer plywood or OSB – 19.2 (488 mm) o.c. joist spacing – use 3/4"(19 mm) tongue and groove nominal thickness.
 - For double layer plywood or OSB – 24" (610 mm) o.c. joist spacing – use double layer plywood or OSB consisting of minimum sub-floor thickness 3/4" (19 mm) nominal thickness, tongue and groove minimum underlayment thickness 3/8" (9 mm) nominal thickness.
 3. Minimum construction for interior natural stone tiled floors as follows: Maximum spacing 24" (610 mm) o.c. double layer wood floor consisting of a minimum sub-floor thickness 3/4" nominal (19 mm) tongue-and-groove with a minimum underlayment thickness 3/8" nominal (10 mm)
- SUB-FLOOR:** 3/4" (19 mm) thick plywood or OSB, either plain with all sheet edges blocked or tongue and groove, over bridged joists spaced 24" (610 mm) o.c. maximum; fasten plywood every 6" (150 mm) o.c. along sheet ends and 8" (200 mm) o.c. along intermediate supports with 8d ring-shank, coated or hot dip galvanized nails (or screws); allow 1/8" (3 mm) between sheet ends and 1/4" (6 mm) between sheets edges; all sheet ends must

be supported by a framing member; glue sheets to joists with construction adhesive.

UNDERLAYMENT: 3/8" (9 mm) thick plugged-faced plywood or OSB fastened every 6" (150 mm) along sheet ends and every 8" (200 mm) in the panel field (both directions) with 8d ring-shank, coated or hot dip galvanized nails (or screws); allow 1/8" (3 mm) to 1/4" (6 mm) between sheets and 1/4" (6 mm) between sheet edges and any abutting surfaces; offset underlayment joists from joints in sub-floor and stagger joints between sheet ends; glue underlayment to sub-floor with construction adhesive. Refer to Technical Data Sheet 152 "Requirements for Direct Bonding of Ceramic or Stone Tiles Over Wood Floors" for complete details.

Installation of STRATA_HEAT™ to the substrate:

1. Install STRATA_HEAT to the substrate using the appropriate ANSI A118.4, ANSI A118.11 or ANSI A118.15 mortar as outlined by the Tile Council of North America for the applicable installation. Mix the mortar on the loose side but still able to hold a notch to enable complete wetting of the STRATA_HEAT fleece layer. Using a LATICRETE® polymer modified mortar apply to the substrate in a thin-bed method using a 1/4" (6 mm) x 3/16" (5 mm) V-notched trowel, or 1/4" (6 mm) x 1/4" (6 mm) square notch trowel, being sure to key the mortar into the substrate. Ensure mortar is "wet-out" sufficiently to allow for optimal bedding of STRATA_HEAT. Spread only enough mortar that can be covered with STRATA_HEAT during the specified open time of the mortar.

2. Embed STRATA_HEAT into the mortar, fabric side down. Using a trowel or screed, apply pressure to ensure proper bedding. To ensure a good bond between the STRATA_HEAT Mat and the substrate, roll the surface with a 50-75 lb. (23-34 kg) floor roller after each section of STRATA_HEAT Mat is installed. Be sure to verify proper coverage beneath the mat. Areas of STRATA_HEAT embedded properly in the mortar will appear darker than areas not embedded; lift occasionally if necessary to verify coverage. Cut mat to appropriate lengths when approaching walls or other objects, leave approximately 1/4" (6 mm) between mat and edge of wall or object for movement.

3. Install adjacent sections of STRATA_HEAT™ in the same manner, being sure to line edges of each section without leaving any gaps.

ESTIMATED THIN-SET COVERAGE

- To embed a 161 ft² (13.9 m²) roll of STRATA_HEAT Mat to the substrate using a 1/4" x 3/16" (6 x 5 mm) V-notch trowel - 1.5 bags will be required
- To embed a 161 ft² (15 m²) roll of STRATA_HEAT Mat to the substrate using a 1/4" x 1/4" (6 x 6 mm) square-notch trowel - 2 bags will be required
- To fill divots and set 161 ft² (15 m²) of tile with a 1/4" x 3/8" (6 x 10 mm) square notch rowel on top of STRATA_HEAT Mat - 4.4 bags will be required
- In total, 5.9 bags will be when required when installing a 161 ft² (15 m²) roll of STRATA_HEAT Mat when

using a 1/4" x 3/16" (6 x 5 mm) V-notch trowel and 1/4" x 3/8" (6 x 10 mm) square notch trowel for tile or

- In total, 6.4 bags will be when required when installing a 161 ft² (15 m²) roll of STRATA_HEAT Mat when using a 1/4" x 1/4" (6 x 6 mm) square-notch trowel and 1/4" x 3/8" (6 x 10 mm) square notch trowel for tile

STRATA_HEAT WIRE INSTALLATION

Follow DS-044.6 STRATA_HEAT Wire Installation Manual when installing the STRATA_HEAT Wire into the STRATA_HEAT Mat.

6. AVAILABILITY AND COST

Availability

LATICRETE materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

- 25 Year System Warranty (US) (English)
- 5 Year System Warranty (US) (English)
- 10 Year System Warranty (US) (English)
- 1 Year Product Warranty (US) (English)
- Lifetime System Warranty (US) (English)

8. MAINTENANCE

Non-finish LATICRETE and LATAPOXY installation materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at laticrete.com. The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty

- DS 230.99: LATICRETE Lifetime System Warranty (United States and Canada)
- DS 025.0: LATICRETE 25 Year System Warranty (United States and Canada)
- DS 230.10: LATICRETE 10 Year System Warranty (United States and Canada)
- DS 230.05: LATICRETE 5 Year System Warranty (United States and Canada)
- DS 259.0: 272 Mortar
- DS 296.0: 253 Gold
- DS 663.0: HYDRO BAN®
- DS 677.0: 254 Platinum
- DS 255.0: 255 Multimax
- TDS 152: Bonding Ceramic Tile, Stone or Brick Over Wood Floor
- DS 614.0: Floor Heat Wire

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2026 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.